




MOTOROL FRONT FORK OIL (SHOCK ABSORBING OIL)

Introduction:

MOTOROL Front Fork Oil is specially developed for hydraulic front forks of motorcycles and similar shock absorbing and damping mechanism as well. Recommended for all types of motorcycles fitted with hydraulic front forks.



Advantages:


- ◆ Provides smooth and comfort riding
- ◆ Dampens the shock and vibrations
- ◆ Longer oil life with increased oxidation stability
- ◆ Protects from wear, corrosion and foaming

Performance Standard:

Proprietary grade

Typical Specifications:

Sr. No.	Characteristics	Test Method	Typ. Value
1	Appearance	VISUAL	Bright & Clear
2	Colour	ASTM D 1500	3.0
3	Kinematic Viscosity at 100°C, cSt	ASTM D - 445	9-10
	Kinematic Viscosity at 40°C, cSt	ASTM D - 445	61-75
5	Viscosity Index, Min	ASTM D 2270	100
6	Flash Point, (COC), °C Min	ASTM D - 92	180
7	Pour Point, °C Max	ASTM D - 97	(-) 21



Environment, Health & Safety:

Every care has been taken to ensure the accuracy of the information in this PDS. This however may be affected by subsequent improvement in product (R&D). MSDS is available for all MOTOROL products on request.

MOTOROL products are unlikely to present any health and safety hazard with proper use for the correct application and maintain proper personal hygiene. Do not Spill oils on the shop floor, discharge into drains ,ground or water sources.