



THRUST (4 STROKE TWO WHEELER ENGINE OIL)

Introduction:

MOTOROL THRUST is a semi - synthetic technology based lubricant designed for all new generation 4 stroke engine oil which enhance shear stability index. Formulated with high viscosity index semi - synthetic base oil & high performance additives meeting API SL, JASO MA2.

Applications:

- ◆ Provides smooth and comfort riding
- ◆ All high performance 4 stroke Two Wheelers
- ◆ Recommended for all Modern, Touring, Seasoned & Classic Bikes
- ◆ Perfect choice for Riders who demand Top Performance.

Advantages:

- ◆ Provides smooth and comfort riding
- ◆ Superior protection to transmission and clutch plates.
- ◆ Smooth gear shift & easy start
- ◆ Cleaner engine & better cooling

Performance Standard:

- ◆ API SL, JASO MA2

Typical Specifications:

Sr. No.	Characteristics	Test Method	10W-40	20W-50
1	Appearance	VISUAL	Bright & Clear	Bright & Clear
2	Colour, Max	ASTM D 1500	3	3
3	Kinematic Viscosity at 100°C, cSt	ASTM D - 445	13.5-15.5	17.5-19.5
4	Viscosity Index, Min	ASTM D - 2270	120	120
5	TBN, mg KOH/g	ASTM D - 2896	7.0-10.0	7.0-10.0
6	Flash Point, (COC), °C Min	ASTM D - 92	220	230
7	Pour Point, °C Max	ASTM D - 97	(-)27	(-)27

Environment, Health & Safety:

Every care has been taken to ensure the accuracy of the information in this PDS. This however may be affected by subsequent improvement in product (R&D). MSDS is available for all MOTOROL products on request.

MOTOROL products are unlikely to present any health and safety hazard with proper use for the correct application and maintain proper personal hygiene. Do not Spill oils on the shop floor, discharge into drains ,ground or water sources.