



MOTOROL HI COOL COOLANT (CONCENTRATE)

Introduction:

Motorol Hi-cool coolant is compatible with any anti freeze /coolant - regardless of colour for use in all makes and models of cars and light duty trucks. This formula provides a high degree of performance, durability and carefully balanced protection against temperature extremes and rust corrosion of all cooling system metals including aluminium.

Applications:

- Hi cool is recommended for passenger cars, commercial vehicles, heavy vehicles and earth moving equipments as a radiator coolant

How to use:


- For desired performance 1 parts of Hi-cool is to be diluted with 3 parts of distilled water in most of the vehicles.

Performance Standard:

Meeting JIS K-2234-1994, IS : 5759-1994

Typical Specifications:

Sr. No.	Characteristics	Typ. Value
1	Appearance	Green Liquid
2	Boling Point, °C Min	155
3	Freezing Point, °C	
	30% Volume Solution	-14
	50% Volume Solution	-34



Environment, Health & Safety:

Every care has been taken to ensure the accuracy of the information in this PDS. This however may be affected by subsequent improvement in product (R&D). MSDS is available for all MOTOROL products on request.

MOTOROL products are unlikely to present any health and safety hazard with proper use for the correct application and maintain proper personal hygiene. Do not Spill oils on the shop floor, discharge into drains ,ground or water sources.